



| | |
|----|------|
| 1 | VSS |
| 2 | VDD |
| 3 | VO |
| 4 | RS |
| 5 | R/W |
| 6 | E |
| 7 | DB0 |
| 8 | DB1 |
| 9 | DB2 |
| 10 | DB3 |
| 11 | DB4 |
| 12 | DB5 |
| 13 | DB6 |
| 14 | DB7 |
| 15 | PSB |
| 16 | NC |
| 17 | /RES |
| 18 | NC |
| 19 | K |
| 20 | A |

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+50°C
- 5.STORAGE TEMP: -20°C--+60°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/32DUTY 1/5BIAS
- 8.DRIVE: ST7920
- 9.BACKLIGHT TYPE: LED
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

| | | | |
|----------------|------|----------------|------------------|
| 北京思普瑞特科技发展有限公司 | | | |
| 绘图: | 型号: | 12864A-1(中文字库) | 单位: mm |
| 审核: | 版本号: | 0 | 电话: 010-51661178 |
| 批准: | 日期: | | 传真: 010-62988681 |