



1	FG	18	DB7
2	VSS	19	FS
3	VDD	20	VOUT
4	VO	21	A
5	/WR	22	K
6	/RD	23	ED
7	/CE	24	CDATA
8	C/D	25	FR
9	NC	26	LP
10	RESET	27	HSCP
11	DB0	28	NC
12	DB1	29	VDD
13	DB2	30	VSS
14	DB3	31	VO
15	DB4	32	VOUT
16	DB5	33	A
17	DB6	34	K

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+60°C
- 5.STORAGE TEMP: -20°C--+70°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 8.DRIVE: T6963C
- 9.BACKLIGHT TYPE: LED(WHITE;5.0±0.1DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

北京思普瑞特科技发展有限公司					
绘图:		型号:	240128A4	单位:	mm
审核:		版号:	0	电话:	010-51661178
批准:		日期:		传真:	010-62988681