



CN2

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

CN1

1	2	3	4	5	6	7	8	9	10
VSS	VDD	VO	/WR	/RD	/CS	A0	RST	D0	D1
11	12	13	14	15	16	17	18	19	20
D2	D3	D4	D5	D6	D7	NC	VOUT	NC	NC

CN3

1	2	3	4	5	6	7	8	9	10	11	12	13	14
FLM	LOAD	CP	M	VO	VDD	VSS	VEE	DB0	DB1	DB2	DB3	DISPOFF	NC



- NOTES:
- |                             |                       |
|-----------------------------|-----------------------|
| 1.DISPLAY TYPE:             | STN/BLUE              |
| 2.VIEWING DIRECTION:        | 6:00                  |
| 3.POLARIZER MODE:           | TRANSMISSIVE/NEGATIVE |
| 4.OPERATING TEMP:           | 0 °C---+50°C          |
| 5.STORAGE TEMP:             | -10 °C---+60°C        |
| 6.VDD:                      | +5V                   |
| 7.DRIVE METHOD:             | 1/240DUTY 1/17BIAS    |
| 8.DRIVE:                    | SED1335FOA            |
| 9.BACKLIGHT:                | CCFL(WHITE)           |
| 10.ALL UNMARKED TOLERANCES: | ±0.3mm                |

北京思普瑞特科技发展有限公司			
绘图:	型号: 320240A-1	单位:	mm
审核:	版本号: 0	电话:	010-51661178
批准:	日期:	传真:	010-62988681