



CON1

1	FRAME	11	D2
2	LOAD	12	D3
3	CP	13	DISPOFF
4	M	14	NC
5	VO	15	NC
6	VDD	16	NC
7	VSS	17	NC
8	VEE	18	VOUT
9	DO	19	NC
10	D1	20	NC

CON2

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

NOTES:

- | | |
|-----------------------------|-----------------------|
| 1.DISPLAY TYPE: | STN/BLUE |
| 2.VIEWING DIRECTION: | 6:00 |
| 3.POLARIZER MODE: | TRANSMISSIVE/NEGATIVE |
| 4.OPERATING TEMP: | 0C--+50°C |
| 5.STORAGE TEMP: | -10C--+60°C |
| 6.VDD: | +5V |
| 7.DRIVE METHOD: | 1/240DUTY 1/17BIAS |
| 8.CONTROLLER: | WITHOUT |
| 9.BACKLIGHT: | CCFL(WHITE) |
| 10.ALL UNMARKED TOLERANCES: | 0.3mm |

北京思普瑞特科技发展有限公司				
绘图:	型号:	320240B(不带1335)	单位:	mm
审核:	版本号:	0	电话:	010-51661178
批准:	版本号:		传真:	010-62988681