



CON1

1	VSS	11	D2
2	VDD	12	D3
3	VO	13	D4
4	/WR	14	D5
5	/RD	15	D6
6	/CS	16	D7
7	A0	17	NC
8	RST	18	VOUT
9	DO	19	NC
10	D1	20	NC

CON2

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

NOTES:

- | | |
|-----------------------------|-----------------------|
| 1.DISPLAY TYPE: | STN/BLUE |
| 2.VIEWING DIRECTION: | 6:00 |
| 3.POLARIZER MODE: | TRANSMISSIVE/NEGATIVE |
| 4.OPERATING TEMP: | 0C---+50.C |
| 5.STORAGE TEMP: | -10C---+60.C |
| 6.VDD: | +5V |
| 7.DRIVE METHOD: | 1/240DUTY 1/17BIAS |
| 8.CONTROLLER: | SED1335FOA |
| 9.BACKLIGHT: | CCFL(WHITE) |
| 10.ALL UNMARKED TOLERANCES: | ±0.3mm |

北京思普瑞特科技发展有限公司			
绘图:	型号:	320240B(带1335)	单位: mm
审核:	版本号:	0	电话: 010-51661178
批准:	版本号:		传真: 010-62988681