



CON2

| | | | |
|---|---------|----|-----|
| 1 | FLM | 8 | D3 |
| 2 | M | 9 | D4 |
| 3 | CL1 | 10 | VDD |
| 4 | CL2 | 11 | VSS |
| 5 | DISPOFF | 12 | VO |
| 6 | D1 | 13 | VEE |
| 7 | D2 | 14 | GND |

CON1

| | | | | | | | | | | | | | | | | | |
|-----|-----|----|-----|-----|-----|----|------|-----|-----|-----|-----|-----|-----|-----|-----|----|------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 |
| VSS | VDD | VO | /WR | /RD | /CS | AO | /RES | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | A | VOUT |

NOTES:

- 1.DISPLAY TYPE: STN Y-G
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C---+70°C
- 5.STORAGE TEMP: -30°C---+80°C
- 6.LCD OPERATING VOLTAGE:-----
- 7.DRIVE METHOD: 1/240DUTY 1/16.27BIAS
- 8.CONTROLLER: SED1335
- 9.BACKLIGHT: CCF/LED
- 10.ALL UNMARKED TOLERANCES:±0.3mm
- 11.BEZEL(THICKNESS:0.6mm) IS TO BE PAINTED BLACK

| | | | | |
|----------------|------|---------|-----|--------------|
| 北京思普瑞特科技发展有限公司 | | | | |
| 绘图: | 型号: | 320240C | 单位: | mm |
| 审核: | 版本号: | 0 | 电话: | 010-51661178 |
| 批准: | 日期: | | 传真: | 010-62988681 |