



1	FG	18	FS
2	VSS	19	VOUT
3	VDD	20	A
4	V \square	21	K
5	/WR	22	NC
6	/RD	23	ED
7	/CE	24	CDATA
8	C/D	25	FR
9	RESET	26	LP
10	DB0	27	HSCP
11	DB1	28	NC
12	DB2	29	VDD
13	DB3	30	VSS
14	DB4	31	V \square
15	DB5	32	VOUT
16	DB6	33	A
17	DB7	34	K

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+60°C
- 5.STORAGE TEMP: -20°C--+70°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 8.DRIVE: T6963C
- 9.BACKLIGHT TYPE: LED(YELLOW-GREEN;5.0±0.1DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

北京思普瑞特科技发展有限公司			
绘图:	型号:	240128A	单位: mm
审核:	版本号:	0	电话: 010-51661178
批准:	日期:		传真: 010-62988681